



**BACHA KHAN MEDICAL COMPLEX /  
GAJJU KHAN MEDICAL COLLEGE  
MEDICAL TEACHING INSTITUTION (MTI)**

Contact No: 0938-280214

**BID SOLICITATION DOCUMENTS  
FOR  
SUPPLY & INSTALLATION OF COMPLETE LAN &  
WI-FI INFRASTRUCTURE**

**Note:** The prospective bidder is expected to examine the Bidding Documents carefully, including all Instructions, Terms & Conditions, and Specifications etc. Failure to furnish all information required by the Bidding documents or submission of a Bid not substantially responsive to the Bidding Documents in every respect would result in the rejection of the Bid.

## Brief Introduction of GKMC & BKMC -MTI

### 1 Overview of RFP:

Gajju Khan Medical College & Bacha Khan Medical Complex – MTI invites RFP response from all bidders for “**The supply & Installation of complete LAN & Wi-Fi Infrastructure**” as per guidelines mentioned in this RFP.

#### 1.1 Proposed Methodology

Bidders will submit a detailed technical proposal including Fiber/Copper Layouts, BoQ with specification compliance as per RFP requirement, previous similar work performed and methodology to complete work. Financial proposal will also be submitted with technical proposal.

#### 1.2 Terms of References (TORs)

1. The Procurement shall be conducted in accordance with the KPPRA Rules 2014 on **Single Stage Two Envelope Procedure**. All Bids must reach in Office at **00 :00AM** on **Date:00-00-0000**
2. GKMC & BKMC invites two separate sealed envelopes, one for Technical Proposal and One for Financial which will be clearly marked outside the envelopes.
3. The Technical bid should clearly mention Make, Model, origin and Brand, (Specification of bid) without quoting the price and must mention the warranty period. (In Case of Hardware)
4. Compliance against each Technical Specifications must be attached.
5. Company seal / stamp must be fixed on Technical Specification and Financial Proposal.
6. Bid Money will be 2% of complete Project Value.
7. **If any firm fails to qualify the Technical Evaluation Criteria based upon ToRs, then financial bid of the same will not be opened.**
8. **Mandatory Requirements are as follows: -**
  - a. Manufacture Authorization Letter MAF/MAL must be attached against Quoted brand.
  - b. OEM partnership letter must be attached against Quoted brand.
  - c. The bidder should provide **SECP** registration Certificate with Technical Proposal.
  - d. The bidder should provide **FBR** registration certificate and ATL proof with Technical Proposal.
  - e. The bidder should provide **KPRA registration** certificate with Technical Proposal.
  - f. The bidder should provide an **undertaking** on stamp paper that it is not blacklisted by any of the Provincial / Federal Government or organization of the state / Federal Government in Pakistan in accordance with the Section 44(1) KPPRA Rules 2014.
  - g. Bids from any bidder who is found or purported to be engaged or under investigation for offences related to fraud, under invoicing, tax evasion,

- concealment, money laundering etc. shall be rejected without assigning any reason.
- h. The bidder must submit **Annual Audited Report** for the last three years.
  - i. Then bidder must submit **Bank Statement with Bank Account Managing letter for** the last three years.
  - j. The bidder shall give at least **three Relevant References** (Purchase Order) of similar equipment delivery / installation by their firm.
  - k. The bidder shall have at least **three-Year Relevant Experience** for the supply of similar equipment.
  - l. **Call Deposit** of Two percent (2%) of the total bid amount must be attached with financial proposal in separate sealed envelope in favor of **Head IT Division**, Customer Name: **on or before 10:00 AM, DD-MM-YYYY.** The EM will be enclosed with Technical Proposal.
9. **Tender bid opening will be held on Wednesday, DD-MM-YYYY at 11:00AM at GKMC & BKMC Islamabad.**
- 10. Any bid submitted after due date and time will not be entertained.**
11. The BKMC / GKMC – MTI will not be responsible for any costs or expenses incurred by bidders in connection with the preparation or delivery of bids.
  12. The prices quoted shall remain valid for **120 days**, after the date of opening of the tender.
  13. Delivery and installation of all items must be made within 30 days for local and 90 days for import item of issuance of purchase order.
  14. All prices quoted must be inclusive of all Taxes applicable, such as GST, Income Tax, etc.
  15. Rate should be quoted in words and figures.
- 16. In case of failure to supply the item under specified time. The work order should be awarded to second lowest.**
17. Failure to supply items within 30 days for local and 90 days' time period, PO will invoke. In addition to that, two percent (2%) Call Deposit (CDR) amount will be forfeited.
18. Bidders must submit the bid that matches or is better than the required specifications
- 19. No negotiations and revised bids will be allowed.**
20. Proposals shall be submitted in English language.
21. The proposals shall be comprehensive, clear, and elaborate. Different sections/Annexures of the proposals shall be separated using color separators, flags, or tags. The proposals shall be prepared without any interlineations or overwriting.
22. The Hospital reserves the right to accept or reject all the proposals submitted at any time in accordance with applicable KPPRA rules.

23. All pages must be Signed & Stamp by the Authorized Authority.

**24. Proposal weightage is Given below:**

| <b>PROPOSAL</b> | <b>WEIGHT</b> |
|-----------------|---------------|
| Technical       | 70%           |
| Financial       | 30%           |
| <b>TOTAL</b>    | <b>100%</b>   |

**25. Contract Period/Warranties:**

- a. Minimum Warranty of the Quoted Equipment is 3 years.

**22. TECHNICAL EVALUATION CRITERIA**

PASSING MARKS: A technically eligible bidder, based on conditions listed in this document, not meeting the 70% pass marks limit will be rejected in Technical Evaluation, and its sealed / unopened Financial Proposal shall be returned. All bidders scoring greater than or equal to 70% of the marks will be accepted in technical proposal, and their financial bids will be opened.

The Bidders who have duly complied with the Eligibility/Qualification and Evaluation Criteria will be eligible for further processing.

The Bids which do not confirm to the Technical Specifications or Bid conditions or the Bids from the Bidders without adequate capabilities for supply and maintenance / warranty /support services will be rejected.

The technical proposals shall be evaluated by the technical evaluation committee in the light of following evaluation criteria.

| <b>Description</b>   | <b>Maximum Points</b> |
|--|-----------------------|
| <b>Legal (Mandatory)</b>   | <b>Mandatory</b>      |
| Certificate of Company/Firm Registration/Incorporation under the laws of Pakistan  |                       |
| Valid Income Tax Registration  |                       |
| Valid General Sales Tax Registration (Status = Active with FBR) with ATL Proof.  |                       |
| KAPRA Registration   |                       |
| Submission of undertaking on legal valid and attested stamp paper that the Firm is not blacklisted by any of Provincial or Federal Government Department, Agency, Organization or autonomous body or Private Sector Organization Anywhere in Pakistan (On100 Rs Stamp Paper) |                       |
| Compliance to the technical specifications of Services to be procured are Mentioned in Annex-A of this document.   |                       |
| In full compliance of the Execution Schedule and Delivery Period mentioned in Tender document (Undertaking)  |                       |
| OEM authorization & partnership certificate for the quoted products  |                       |
| OEM (Warehouse) or Bidder's Office presence must have in major cities of Pakistan.   |                       |
| Certificates must be provided: ISO 9001: 2015, Fair Price and Original Equipment undertaking. (On100 Rs Stamp Paper)   |                       |

|   |             |
|---|-------------|
| <b>Successful Completed ICT Projects similar nature</b><br>16 - 20 ICT Projects – 10<br>11 - 15 ICT Projects – 07<br>6 - 10 ICT Projects– 05<br>Less than 10 - 00 | 10          |
| <b>Human Resource:</b><br>Team Leader – 5 (2.5 marks for each)<br>IT Engineer – 6 (2 marks for each)<br>IT Technician – 4 (1 mark for each)                       | 5<br>6<br>4 |
| The bidder should have at least one deployment of the similar quoted equipment / project in the teaching hospital   | 10          |
| <b>Company operating in Pakistan:</b><br>10 (Ten) Years – 10<br>(One mark for each year)  | 10          |
| <b>Location of offices in Peshawar / Islamabad / Rawalpindi:</b><br>Office Presence – 05<br>No Presence-0   | 05          |
| <b>Annual Turnover:</b><br>Minimum 500 Million – 15<br>Minimum 250 Million – 7.5  | 15          |
| Performances certificate of the quoted project<br>(one mark for each )  | 05          |
| <b>Total</b>  | <b>70</b>   |

Passing Marks in Technical Proposal = 49 /70

**1.3 BRIEF SCOPE OF WORK for LAN & WI-FI Infrastructure:**

- i. GKMC & BKMC is interested to establish Wi-Fi infrastructure in their College & Hospital Premises.
- ii. At the time of installation and commissioning, Selected Bidder must provide comprehensive survey documentation of deployments laid including logical Diagrams, HLDS, LLDS, labelling, schematics, and configuration, SOPs, as part of Scope of Work.
- iii. Operation and maintenance of the equipment infrastructure will be the sole responsibility of the selected bidder.

**3. PRE-DEPLOYMENT ACTIVITIES:**

- i. Detailed implementation plan shall be provided within seven (07) days from the date of acceptance of site surveys and BOQ are finalized / accepted by GKMC & BKMC.
- ii. Selected bidder will provide complete solution of network integration including deployment & configuration.
- iii. If the Selected Bidder do not meet the requirements as per the survey report submitted on which the BoQ was finalized, then the requirement shall be met on Selected Bidder's cost.

**4. POST-CONTRACT ACTIVITIES:**

- i. Passive services and the related passive equipment will be provided by selected bidder.
- ii. The deployment of GKMC & BKMC must be completed in 8-10-week times upon issuance of LOI/LOA from all aspects and service delivery shall be started.
- iii. Selected bidder must Provide a dedicated Account Manager to GKMC & BKMC for any Query.

**5. NETWORK COMMISSIONING REQUIREMENT**

Network topology will be based on interconnected Nodes through I2/I3 switches. The selected bidder must design and configure:

- i. Active and passive equipment supply and installation at mentioned location as per scope.
- ii. Selected bidder will provide complete solution of network integration including deployment, configuration integration with existing network, setting up server and configuring as per the given requirements.
- iii. These network commissioning requirements can be modified or removed based on design finalization between bidder and customer with commercial impact.

**6. PROJECT EXECUTION REQUIREMENTS**

- i. Payments will be made onetime bases agreed terms; however, the Selected Bidder will be solely responsible for deploying system/equipment and to maintain warranties and provisioning of services for up to three (03) years.
- ii. Selected bidder must design and deploy network configuration plan along with configuration design and submit/ present the same for the approval to GKMC & BKMC.
- iii. After complete site surveys, BoQ will be finalized for each site as per the site requirement and will be made part of contract agreement through an Amendment.

## Bid Security Form

Whereas [name of the Bidder] (hereinafter called "the Bidder") has submitted its bid dated [date of submission of bid] for the supply of [name and/or description of the goods] (hereinafter called "the Bid").

KNOW ALL PEOPLE by these presents that WE [name of bank] of [name of country], having our registered office at [address of bank] (hereinafter called "the Bank"), are bound unto [name of Procuring agency] (hereinafter called "the Procuring agency") in the sum of for which payment well and truly to be made to the said Procuring agency, the Bank binds itself, its successors, and assigns by these presents. Sealed with the Common Seal of the said Bank this \_\_\_\_\_ day of \_\_\_\_\_ 20\_\_\_\_\_.

THE CONDITIONS of this obligation are:

1. If the Bidder withdraws its Bid during the period of bid validity specified by the Bidder on the Bid Form; or
2. If the Bidder, having been notified of the acceptance of its Bid by the Procuring agency during the period of bid validity:
  - a. fails or refuses to execute the Contract Form, if required; or
  - b. fails or refuses to furnish the performance security, in accordance with the Instructions to Bidders;

We undertake to pay to the Procuring agency up to the above amount upon receipt of its first written demand, without the Procuring agency having to substantiate its demand, provided that in its demand the Procuring agency will note that the amount claimed by it is due to it, owing to the occurrence of one or both of the two conditions, specifying the occurred condition or conditions.

This guarantee will remain in force up to and including twenty eight (28) days after the period of bid validity, and any demand in respect thereof should reach the Bank not later than the above date.

---

*[signature of the bank]*

## Performance Security Form

To: *[name of Procuring agency]*

WHEREAS *[name of Supplier]* (hereinafter called "the Supplier") has undertaken, in pursuance of Contract No. *[reference number of the contract]* dated \_\_\_\_\_ 20\_\_\_\_ to supply *[description of goods and services]* (hereinafter called "the Contract").

AND WHEREAS it has been stipulated by you in the said Contract that the Supplier shall furnish you with a bank guarantee by a reputable bank for the sum specified therein as security for compliance with the Supplier's performance obligations in accordance with the Contract.

AND WHEREAS we have agreed to give the Supplier a guarantee:

THEREFORE, WE hereby affirm that we are Guarantors and responsible to you, on behalf of the Supplier, up to a total of *[amount of the guarantee in words and figures]*, and we undertake to pay you, upon your first written demand declaring the Supplier to be in default under the Contract and without cavil or argument, any sum or sums within the limits of *[amount of guarantee]* as aforesaid, without your needing to prove or to show grounds or reasons for your demand or the sum specified therein.

This guarantee is valid until the \_\_\_\_\_ day of \_\_\_\_\_ 20\_\_\_\_\_.

Signature and seal of the Guarantors

---

*[name of bank or financial institution]*

---

*[Address]*

---

*[date]*



## Contract Form

THIS AGREEMENT made the \_\_\_\_\_ day of \_\_\_\_\_ 19\_\_\_\_ between *[name of Procuring Agency]* Of *[country of Procuring agency]* (hereinafter called “the Procuring agency”) of the one part and *[name of Supplier]* Of *[city and country of Supplier]* (hereinafter called “the Supplier”) of the other part:

WHEREAS the Procuring agency invited bids for certain goods and ancillary services, viz., *[brief description of goods and services]* and has accepted a bid by the Supplier for the supply of those goods and services in the sum of *[contract price in words and figures]* (hereinafter called “the Contract Price”).

NOW THIS AGREEMENT WITNESSETH AS FOLLOWS:

1. In this Agreement words and expressions shall have the same meanings as are respectively assigned to them in the Conditions of Contract referred to.
2. The following documents shall be deemed to form and be read and construed as part of this Agreement, viz.:
  - (a) the Bid Form and the Price Schedule submitted by the Bidder;
  - (b) the Schedule of Requirements;
  - (c) the Technical Specifications;
  - (d) the General Conditions of Contract;
  - (e) the Special Conditions of Contract; and
  - (f) the Procuring agency’s Notification of Award.
3. In consideration of the payments to be made by the Procuring agency to the Supplier as hereinafter mentioned, the Supplier hereby covenants with the Procuring agency to provide the goods and services and to remedy defects therein in conformity in all respects with the provisions of the Contract
4. The Procuring agency hereby covenants to pay the Supplier in consideration of the provision of the goods and services and the remedying of defects therein, the Contract Price or such other sum as may become payable under the provisions of the contract at the times and in the manner prescribed by the contract.

IN WITNESS whereof the parties hereto have caused this Agreement to be executed in accordance with their respective laws the day and year first above written.

Signed, sealed, delivered by \_\_\_\_\_ the \_\_\_\_\_ (for the Procuring Agency)

Signed, sealed, delivered by \_\_\_\_\_ the \_\_\_\_\_ (for the Supplier)

**Payment:**

Payment will be made after successful completion, installation and inspection of the project.

No advance payment will be made.

## 1.4 Bill of Materials:

### 1.4.1 Active Items:

| Sr. No | Description   | A/U | QTY |
|--------|---|-----|-----|
| 1      | Router  | No  | 1   |
| 2      | Firewall with 1-year Licenses (AV, IPS, URL and Application)                                | No  | 1   |
| 3      | Core Switch   | No  | 1   |
| 4      | Aggregation Switch  | No  | 4   |
| 5      | 8 port Access Switch  | No  | 40  |
| 6      | 24 port Access Switch   | No  | 30  |
| 7      | 48 port Access Switch   | No  | 8   |
| 8      | Wi-Fi Controller  | No  | 1   |
| 9      | Access Points with Power Adapter  | No  | 144 |
| 10     | SFP 1G  | No  | 142 |
| 11     | SFP 10G   | No  | 12  |
| 12     | Campus management.  | No  | 1   |
| 13     | NMS for Network   | No  | 1   |
| 14     | Server for NMS  | No  | 1   |
| 15     | Server for HMIS   | No  | 2   |
| 16     | SAN Storage   | No  | 1   |
| 17     | Windows Server Std 2022, 64Bit English 1pk DSP OEI DVD 16 core, along with Hyper V license. | No  | 3   |
| 18     | 5KVA UPS in IT Room with 4 hours backup   | No  | 1   |
| 19     | 650 VA UPS for Cabinets   | No  | 68  |
| 20     | 5KVA AVR  | No  | 1   |
| 21     | Laptop Systems (Network Administration)   | No  | 4   |
| 22     | 55-inch or more LED   | No  | 2   |
| 23     | Fire detection system   | No  | 1   |

**1.4.2 Passive Items:**

| Sr. No | Description   | A/U | QTY    |
|--------|---|-----|--------|
| 1      | CAT 6 I/O   | No  | 670    |
| 2      | 3-meter Fiber Patch Cord.   | No  | 200    |
| 3      | CAT 6 Face Plate and Back Box   | No  | 670    |
| 4      | CAT 6 Cable Roll. (305 meter)   | No  | 131    |
| 5      | CAT 6 1meter Patch Cord.  | No  | 670    |
| 6      | 24 Port patch Panel with I/O  | No  | 80     |
| 7      | Cabinet 6U with PDU   | No  | 67     |
| 8      | Cabinet 9U with PDU   | No  | 2      |
| 9      | Cabinet 42U with PDU - supported 8 port KVM switch and drawer   | No  | 2      |
| 10     | Power Socket  | No  | 71     |
| 11     | Power Cable 3.29 dual core. (90 meter)  | No  | 50     |
| 12     | Cable Manager   | No  | 79     |
| 13     | Duct 16x25  | FT  | 10,000 |
| 14     | Duct 16x38  | FT  | 8,000  |
| 15     | Duct 40x40  | FT  | 2,000  |
| 16     | <ul style="list-style-type: none"> <li>a) Active and Passive Items installation including Configuration, Commissioning and Testing.</li> <li>b) Soft/Hard Digging of Fiber including HDPE Pipe, warning tape, Hand Hole, fiber Joints Enclosures, splicing, marker post and reinstate of roads/pavements.</li> <li>c) Power Earthing/Grounding of server room</li> <li>d) 10 days extensive training of GKMC/BKMC ICT staff on installed equipment's and deployed solutions. Preparation and sharing of required user manuals/troubleshooting guide for the installed equipment's.</li> </ul> | Job | 1      |

## 1.5 Annexure:

Below are the all annexures which need to submit with technical Proposal in the form of compliances:

| Sr. No              | Description                      | Annexures |
|---------------------|----------------------------------|-----------|
| <b>Active Items</b> |                                  |           |
| 1                   | Router                           | Annex-A   |
| 2                   | Firewall                         | Annex-B   |
| 3                   | Core Switch                      | Annex-C   |
| 4                   | Aggregation Switch               | Annex-D   |
| 5                   | 8 port Access Switch             | Annex-E   |
| 6                   | 24 port Access Switch            | Annex-E   |
| 7                   | 48 port Access Switch            | Annex-E   |
| 8                   | Wi-Fi Controller                 | Annex-F   |
| 9                   | Access Points with Power Adapter | Annex-G   |
| 10                  | Secure Web Gateway.              | Annex-H   |
| 11                  | NMS for Network                  | Annex-I   |
| 12                  | Server                           | Annex-J   |
| 13                  | SAN Storage                      | Annex-K   |
| 14                  | Laptop Systems                   | Annex-L   |
| 15                  | Fire detection System            | Annex -M  |
| 16                  | 5 KVA UPS                        | Annex - N |
| 17                  | Passive Items                    | Annex- O  |

## 1.6 MINIMUM PRODUCT FEATURE RATING

Following specifications of equipment are base line specifications for the equipment to be deployed.

**(Annexure A)**

| Annex-A                        |  | Router   |
|--------------------------------|--|--|
| Sr.No                          | Description                              | Required   |
| <b>Hardware Specifications</b> |  |  |
| 1                              | CPU                                      | 1.3GHz or more   |
| 2                              | Forwarding Performance In Service (IMIX) | 800Mbps or more  |
| 3                              | Memory                                   | 1GB or more  |
| 4                              | Flash                                    | 256MB or more  |
| 5                              | USB port                                 | 1  |
| 6                              | WAN ports                                | 1 × GE copper port and 1 × GE combo port   |
| 7                              | LAN ports                                | 4 × GE ports(can be configured as WAN interfaces)  |
| 8                              | Operating temperature                    | 0°C to 45°C (32°F to 113°F)  |
| 9                              | Operating humidity                       | 5% RH to 95% RH, non-condensing  |
| <b>Software Specifications</b> |  |  |
| 1                              | Layer 2 switching                        | Ethernet, Ethernet II, VLAN (port-based VLAN, guest VLAN), 802.3x, 802.1p, 802.1Q, 802.1X, STP (802.1D), RSTP (802.1w), MSTP (802.1s), PPP, PPPoE client, PPPoE server, and DDR  |
| 2                              | IP services                              | Unicast/multicast, TCP, UDP, IP option, IP unnumbered, policy-based routing, NetStream, and sFlow  |
| 3                              | IP application                           | Ping, Tracert, ICMP, DHCP server, DHCP relay, DHCP client, DNS client, DNS proxy, DDNS, NTP, and SNTP  |
| 4                              | IPv4 routing                             | Static routing<br>Dynamic routing: RIPv1/v2, OSPFv2, BGP, IS-IS<br>Route iteration<br>Policy routing<br>Equal-cost multi-path routing (ECMP)<br>Multicast routing: IGMPv1/v2/v3, PIM-DM, PIM-SM, MBGP, MSDP  |
| 5                              | QoS                                      | FIFO, WFQ, CBQ<br>Generic Traffic Shaping (GTS)<br>Traffic classification  |
| 6                              | Security                                 | PPPoE client & server, portal, 802.1X<br>Local authentication, RBAC, RADIUS, TACACS+<br>Basic Firewall Function, ASPF, ACL, filter, connection limit<br>IKE, IPsec<br>L2TP, NAT/NAPT, PKI, RSA, SSH v1.5/2.0, URPF, mGRE, GRE<br>ARP attack prevention<br>SSL VPN, ADVPN, GDVPN<br>AES, DES, 3DES, MD5, SHA1 |

|   |                            |   |
|---|----------------------------|---|
| 7 | MPLS                       | LDP, Static LSP<br>L3VPN: Inter-AS MPS VPN (Option 1/2/3), MPLS nested VPN, hierarchy of PE (HoPE), dual-homed CE, MCE, and multirole host<br>L2VPN: Martini, Kompella, CCC PWs and static PWs<br>MPLS TE, RSVP TE  |
| 8 | High availability          | VRRP, VRRPv3<br>Bandwidth-based load balancing and backup<br>IP address-based load balancing and backup<br>NQA collaboration with routing, VRRP or interface backup   |
| 9 | Management and Maintenance | SNMP v1/v2c/v3, MIB, SYSLOG, RMO<br>BiMS remote management, booting from USB drive<br>CLI, file system, and dual image<br>DHCP, FTP, HTTP, ICMP, UDP public, UDP private, TCP public, TCP private, and SNMP<br>Console port login, Telnet (VTY) login, SSH login, and FTP login |

**(Annexure B)**

| <b>Annex-B</b>                 |                    | <b><u>Firewall</u></b>  |
|--------------------------------|--------------------|---|
| <b>Sr. No</b>                  | <b>Description</b> | <b>Required</b>   |
| <b>Hardware Specifications</b> |                    |   |
| 1                              | Ports              | 1 × Console port (CON)<br>2 × Management port<br>12 × Gigabit Ethernet fiber ports<br>14 × Gigabit Ethernet copper ports<br>4 × 10-Gigabit Ethernet fiber ports                         |
| 2                              | Interface modules  | 4-port GE PFC interface module<br>4-port GE fiber interface module<br>4-port 10-GE fiber interface module<br>6-port 10-GE fiber interface module  |
| 3                              | Flash              | 4GB   |
| 4                              | SDRAM              | 8G  |
| 5                              | Temperature        | Operating: 0°C to 45°C (32°F to 113°F)<br>Storage: -40°C to +70°C (-40°F to +158°F)   |
| 6                              | Power Supply       | Dual hot-swappable, AC or DC  |
| <b>Software Specifications</b> |                    |   |
| 1                              | Operation modes    | Route, transparent, and hybrid  |
| 2                              | AAA                | Portal authentication<br>RADIUS authentication<br>HWTACACS authentication<br>PKI/CA (X.509 format) authentication<br>Domain authentication<br>CHAP authentication<br>PAP authentication |



|   |                           |   |
|---|---------------------------|---|
| 3 | Firewall                  | <p>SOP virtual firewall technology, which supports full virtualization of hardware resources, including CPU, memories, and storage</p> <p>Security zone allocatio</p> <p>Protection against malicious attacks, such as land, smurf, fraggle, ping of death, teardrop, IP spoofing, IP fragmentation, ARP spoofing, reverse ARP lookup, invalid TCP flag, large ICMP packet, address/port scanning, SYN flood, ICMP flood, UDP flood, and DNS query flood</p> <p>Basic and advanced ACL</p> <p>Time range-based ACL</p> <p>User-based and application-based access control</p> <p>ASPF application layer packet filtering</p> <p>Static and dynamic blacklist function</p> <p>MAC-IP binding</p> <p>MAC-based ACL</p> <p>MAC-Limitation</p> <p>802.1Q VLAN transparent transmission</p> <p>Bandwidth control</p> |
| 4 | Antivirus                 | <p>Signature-based virus detection</p> <p>Manual and automatic upgrade for the signature database</p> <p>Stream-based processing</p> <p>Virus detection based on HTTP, FTP, SMTP, and POP3</p> <p>Virus types include Backdoor, Email-Worm, IM-Worm, P2P-Worm, Trojan, AdWare, and Virus</p> <p>Virus logs and reports</p>  |
| 5 | Deep intrusion prevention | <p>Prevention against common attacks such as hacker, worm/virus, Trojan, malicious code, spyware/adware, DoS/DDoS, buffer overflow, SQL injection, and IDS/IPS bypass</p> <p>Attack signature categories (based on attack types and target systems) and severity levels (including high, medium, low, and notification)</p> <p>Manual and automatic upgrade for the attack signature database (TFTP and HTTP).</p> <p>P2P/IM traffic identification and control</p>   |

|   |   |   |
|---|---|---|
| 6 | Email/webpage/application layer filtering | <p>Email filtering</p> <p>SMTP email address filtering</p> <p>Email subject/content/attachment filtering</p> <p>Webpage filtering</p> <p>HTTP URL/content filtering</p> <p>Java blocking</p> <p>ActiveX blocking</p> <p>SQL injection attack prevention</p>   |
| 7 | NAT                                       | <p>Many-to-one NAT, which maps multiple internal addresses to one public address</p> <p>Many-to-many NAT, which maps multiple internal addresses to multiple public addresses</p> <p>One-to-one NAT, which maps one internal address to one public address</p> <p>NAT of both source address and destination address</p> <p>External hosts access to internal servers</p> <p>Internal address to public interface address mapping</p> <p>NAT support for DNS</p> <p>Setting effective period for NAT</p> <p>NAT ALGs for NAT ALG, including DNS, FTP, H.323, ILS, MSN, NBT, PPTP, and SIP</p> |
| 8 | VPN                                       | <p>L2TP VPN</p> <p>IPSec VPN</p> <p>GRE VPN</p> <p>SSL VPN</p>  |
| 9 | IPSEC VPN                                 | <p>ESP-DES-CBC/ESP-3DES-CBC/ESP-AES-128-CBC/ESP-AES-192-CBC/ESP-AES-256-CBC/ESP-AES-128-GCM/ESP-NULL/SM1-cbc-128/SM4-cbc</p>  |

|    |                          |  |
|----|--------------------------|--|
| 10 | IPv6                     | <p>IPv6 status firewall</p> <p>IPv6 attack protection</p> <p>IPv6 forwarding</p> <p>IPv6 protocols such as ICMPv6, PMTU, Ping6, DNS6, TraceRT6, Telnet6, DHCPv6 Client, and DHCPv6 Relay</p> <p>IPv6 routing: RIPng, OSPFv3, BGP4+, static routing, policy-based routing</p> <p>IPv6 multicast: PIM-SM, and PIM-DM</p> <p>IPv6 transition techniques: NAT-PT, IPv6 tunneling, NAT64 (DNS64), and DS-LITE</p> <p>IPv6 security: NAT-PT, IPv6 tunnel, IPv6 packet filter, RADIUS, IPv6 zone pair policies, IPv6 connection limit</p> |
| 11 | IEEE                     | IEEE 802.1X  |
| 12 | High availability        | <p>SCF 2:1 virtualization</p> <p>Active/active and active/standby stateful failover</p> <p>Configuration synchronization of two firewalls</p> <p>IKE state synchronization in IPsec VPN</p> <p>VRRP</p>  |
| 13 | Configuration management | <p>Configuration management at the CLI</p> <p>Remote management through Web</p> <p>Device management through H3C IMC SSM</p> <p>SNMPv3, compatible with SNMPv2 and SNMPv1</p> <p>Intelligent security policy</p>   |

**(Annexure C)**

| <b>Annex-C</b>                 |                              | <b>Core Switch</b>                                      |
|--------------------------------|------------------------------|---|
| <b>Sr.No</b>                   | <b>Description</b>           | <b>Required</b>   |
| <b>Hardware Specifications</b> |                              |   |
| 1                              | CPU                          | Dual Core, 1.6GHz                                       |
| 2                              | Box Switching capacity       | 2.56Tbps  |
| 3                              | Port Switching capacity      | 960Gbps   |
| 4                              | Packet forwarding rate       | 705Mpps   |
| 5                              | Service ports                | 24 × 1/10GE SFP+ fiber ports<br>2 × QSFP+ fiber ports   |
| 6                              | Stacking bandwidth           | Maximum 480Gbps   |
| 7                              | Fan Trays                    | 2 hot swappable fan trays, invertible airflow           |
| 8                              | Operating Temperature        | 0°C to 45°C (32°F to 113°F)                             |
| 9                              | Storage Temperature          | -40°C to 70°C (-40°F to 158°F)                          |
| 10                             | Operating & storage humidity | 5% RH to 95% RH, non-condensing                         |
| 11                             | Power                        | Dual AC   |
| <b>Software Specifications</b> |                              |   |
| 1                              | VxLAN                        | VXLAN Layer 2 switching                                 |
|                                |                              | VXLAN routing switching                                 |
|                                |                              | VXLAN gateway   |
|                                |                              | Centralized VXLAN control through OpenFlow+Netconf      |
| 2                              | Virtualization               | Intelligent Resilient Framework 2 (IRF2)                |
|                                |                              | Distributed device management                           |
|                                |                              | Distributed link aggregation                            |
|                                |                              | Distributed resilient routing                           |
|                                |                              | Stacking through standard Ethernet ports                |
|                                |                              | Local device stacking and remote device stacking        |
| 3                              | Link aggregation             | LACP-, BFD-, and ARP-based multi-active detection (MAD) |
|                                |                              | 10GE/40GE/100GE port aggregation                        |
| 4                              | Jumbo frame                  | Static aggregation                                      |
|                                |                              | Supported   |
| 5                              | MAC address table            | Max. 256K MAC address entries                           |
|                                |                              | Static MAC address                                      |
|                                |                              | Blackhole MAC address                                   |
|                                |                              | MAC learning limit                                      |
| 6                              | Openflow                     | Openflow1.3   |
| 7                              | VLAN                         | Port-based VLAN (up to 4094 VLANs)                      |
|                                |                              | Default VLAN  |
|                                |                              | QinQ and flexible QinQ                                  |

|     |                    |  |
|-----|--------------------|--|
|     |                    | VLAN mapping   |
|     |                    | PVST+ and RPVST+   |
| 8   | Traffic monitoring | sFLOW  |
| 9   | LLDP               | LLDP/LLDP-MED  |
| 10  | DHCP               | DHCP client  |
|     |                    | DHCP snooping  |
|     |                    | DHCP relay   |
|     |                    | DHCP server  |
|     |                    | DHCP snooping Option 82/DHCP relay Option 82   |
| 11  | ARP                | Max. 128K ARP  |
|     |                    | Static entry   |
|     |                    | Gratuitous ARP   |
|     |                    | Common proxy ARP and local proxy ARP   |
|     |                    | Dynamic ARP inspection   |
|     |                    | ARP anti-attack  |
|     |                    | ARP source suppression   |
| 12  | Routing            | ARP detection based on DHCP snooping safety entries, 802.1X entries, and IP/MAC static binding entries |
|     |                    | Max. 128K IPV4 routing entries   |
|     |                    | Max. 64K IPV6 routing entries  |
|     |                    | IPv4/IPv6 static routing   |
|     |                    | Dynamic routing such as RIP v1/2 and RIPng   |
|     |                    | Policy routing   |
|     |                    | Equal-cost multi-path routing (ECMP)   |
|     |                    | VRRP   |
|     |                    | OSPFv1/v2/v3   |
| BGP |                    |  |
| 13  | IPv6               | IS-IS  |
|     |                    | Neighbor Discovery (ND)  |
|     |                    | PMTU   |
|     |                    | ICMP v6, Telnet v6, SFTP v6, SNMP v6, BFD v6, VRRP v3  |
|     |                    | IPv6 Portal  |
|     |                    | IPv6 tunnel  |
| 14  | Multicast          | IPV6 SAVI  |
|     |                    | IGMP Snooping v2/v3  |
|     |                    | IGMP Snooping fast-leave   |
|     |                    | IGMP Snooping group-policy   |
|     |                    | PIM-SM and PIM-SSM   |
|     |                    | PIM snooping   |
|     |                    | MVRP (GVRP analog)   |
| MFF |                    |  |
|     |                    | Enhanced Layer 3 multicast   |

|    |   |  |
|----|---|--|
| 15 | MPLS  | Support MPLS   |
|    |   | Support MCE  |
|    |   | Support MPLS VPN, VPLS   |
| 16 | Zero configuration                            | DHCP auto-config   |
|    |   | CWMP-TR069   |
| 17 | Broadcast/Multicast/Unicast storm suppression | Storm suppression based on port bandwidth percentage   |
|    |   | Storm suppression based on PPS   |
|    |   | Storm suppression based on BPS   |
| 18 | Loop-free redundant Layer 2 topology          | STP/RSTP/MSTP  |
|    |   | STP Root Guard   |
|    |   | BPDU Guard   |
|    |   | BPDU Blocking and Root Guard   |
|    |   | Link Detection (UDLD)  |
|    |   | Digital Diagnostic Monitor (DDM)   |
| 19 | QoS/ACL                                       | G.8032 Ethernet ring protection switching (ERPS)   |
|    |   | Rate limit for receiving and transmitting packets  |
|    |   | CAR  |
|    |   | Eight output queues per port   |
|    |   | Flexible queue scheduling algorithms based on both port and queue, including SP, WDRR, WRR, WFQ, and SP+WRR      |
|    |   | 802.1p priority and DSCP priority  |
|    |   | Layer 2 to Layer 4 packet filtering  |
|    |   | Traffic classification based on source MAC, destination MAC, source IP, destination IP, port, protocol, and VLAN |
| 20 | Mirroring                                     | Time range   |
|    |   | WRED   |
|    |   | Flow mirroring   |
|    |   | N:4 port mirroring   |
|    |   | Local port mirroring and remote port mirroring   |
|    |   | Policy-based Mirroring   |

**(Annexure D)**

| <b>Annex-D</b>   |   | <b>Aggregation Switch</b>   |
|--|---|---|
| <b>Sr. No</b>  | <b>Description</b>                            | <b>Required</b>   |
| <b>Hardware Specifications</b>   |   |   |
| 1  | CPU   | Dual Core, 800MHz   |
| 2  | Box switching capacity                        | 598Gbps   |
| 3  | Port switching capacity                       | 288Gbps   |
| 4  | Service ports                                 | 24 × SFP ports (including 8 combo interfaces) 4 × 10G SFP+ ports        |
| <b>Software Specifications</b>   |   |   |
| 1  | VxLAN   | VXLAN L2 switching  |
|  |   | VXLAN L3 routing  |
|  |   | VXLAN VTEP  |
|  |   | IS-IS+ENDP distributed control plane                                    |
|  |   | MP-BGP+EVPN distributed control plane                                   |
|  |   | OpenFlow+Netconf centralized control plane                              |
| 2  | Link aggregation                              | 1G/10G/40G port aggregation   |
|  |   | Static aggregation  |
|  |   | Dynamic aggregation   |
|  |   | Multichassis link aggregation   |
| 3  | Broadcast/Multicast/Unicast storm suppression | Storm suppression based on port bandwidth percentage                    |
|  |   | Storm suppression based on PPS  |
|  |   | Storm suppression based on BPS  |
|  |   | Broadcast traffic/Multicast traffic/Unknown unicast traffic suppression |
| 4  | Jumbo frame                                   | A maximum of 10000 bytes  |
| 5  | MAC address table                             | 64K MAC address entries   |
|  |   | Static MAC address  |
|  |   | Blackhole MAC address   |
|  |   | MAC learning limit  |
| 6  | ARP Table                                     | ARP entries: 32K  |
|  |   | Static entry  |
|  |   | Gratuitous ARP  |
|  |   | Common proxy ARP and local proxy ARP                                    |
|  |   | Dynamic ARP inspection  |
|  |   | ARP anti-attack   |
|  |   | ARP flood suppression   |
|  |   | ARP source suppression  |
| ARP detection based on DHCP snooping safety entries, 802.1X entries, and IP/MAC static binding entries |   |   |
| 7  | VLAN  | Port-based VLAN (up to 4094 VLANs)                                      |
|  |   | MAC-based VLAN  |

|    |                                      |  |
|----|--------------------------------------|--|
|    |                                      | Protocol-based VLAN  |
|    |                                      | IP subnet based VLAN   |
|    |                                      | QinQ and flexible QinQ   |
|    |                                      | VLAN mapping   |
|    |                                      | Voice VLAN   |
|    |                                      | MVRP ((GVRP analog))   |
| 8  | Loop-free redundant Layer 2 topology | STP/RSTP/MSTP  |
|    |                                      | STP Root Guard   |
|    |                                      | BPDU Guard   |
|    |                                      | BPDU Blocking and Root Guard   |
|    |                                      | Link Detection (UDLD)  |
|    |                                      | Digital Diagnostic Monitor (DDM)   |
|    |                                      | G.8032 Ethernet ring protection switching (ERPS)   |
| 9  | DHCP                                 | DHCP client  |
|    |                                      | DHCP snooping  |
|    |                                      | DHCP relay   |
|    |                                      | DHCP server  |
|    |                                      | DHCP snooping Option 82/DHCP relay Option 82   |
| 10 | IRF2                                 | IRF2   |
|    |                                      | Distributed device management, distributed link aggregation, and distributed resilient routing |
|    |                                      | Stacking through standard Ethernet interfaces  |
|    |                                      | Local device stacking and remote device stacking   |
|    |                                      | Support up to 9 devices stacking   |
| 11 | IP routing                           | IPv4 routing number 32K  |
|    |                                      | IPv6 routing number 16K  |
|    |                                      | Static routing   |
|    |                                      | RIPv1/v2 and RIPng   |
|    |                                      | OSPFv1/v2/v3   |
|    |                                      | BGP and BGP4+ for IPv6   |
|    |                                      | Equal-cost multi-path routing (ECMP) and policy routing  |
|    |                                      | VRRP/VRRPv3  |
| 12 | IPv6                                 | Neighbor Discovery (ND)  |
|    |                                      | PMTU   |
|    |                                      | IPv6-Ping, IPv6-Tracert, IPv6-Telnet, and IPv6-TFTP  |
|    |                                      | Manual tunnel  |
|    |                                      | 6to4 tunnel  |
|    |                                      | ISATAP tunnel  |
|    |                                      | GRE tunnel   |
| 13 | Multicast                            | IGMP Snooping v1/v2/v3 and MLD Snooping v1/v2  |
|    |                                      | PIM Snooping   |



|    |           |  |
|----|-----------|--|
|    |           | MLD Proxy  |
|    |           | Multicast VLAN   |
|    |           | IGMP v1/v2/v3 and MLD v1/v2  |
|    |           | PIM-DM, PIM-SM and PIM-SSM   |
|    |           | MSDP and MSDP for IPv6   |
|    |           | MBGP and MBGP for IPv6   |
| 14 | MPLS      | Support MPLS   |
|    |           | Support MCE  |
|    |           | Support MPLS VPN, VPLS   |
| 15 | Mirroring | Flow mirroring   |
|    |           | N:4 port mirroring   |
|    |           | Local port mirroring and remote port mirroring   |
|    |           | Policy-based Mirroring   |
|    |           | Traffic Mirroring  |
| 16 | QoS/ACL   | Layer 2 to Layer 4 packet filtering  |
|    |           | Traffic classification based on source MAC, destination MAC, source IP, destination IP, TCP/UDP port, and VLAN |
|    |           | Time range-based ACL   |
|    |           | Bi-directional ACLs (inbound and outbound)   |
|    |           | VLAN-based ACL issuing   |
|    |           | Rate limit for receiving and transmitting packets (a minimum CIR of 8 Kbps)                                    |
|    |           | Packet redirection   |
|    |           | 802.1p priority and DSCP priority  |
|    |           | Committed Access Rate (CAR)  |
|    |           | Flexible queue scheduling algorithms based on both port and queue, including SP, WRR, and SP+WRR               |
| 17 | Security  | Hierarchical user management and password protection   |
|    |           | MAC-based authentication   |
|    |           | 802.1X   |
|    |           | Storm constrain  |
|    |           | Guest VLAN   |
|    |           | AAA authentication   |
|    |           | RADIUS authentication  |
|    |           | HWTACACS   |
|    |           | SSH 2.0  |
|    |           | Port isolation   |
|    |           | Port security  |
|    |           | EAD  |
|    |           | Dynamic ARP detection  |
|    |           | BPDU guard and root guard  |
|    |           | uRPF   |
|    |           | IP/Port/MAC binding  |

|                    |                            |  |
|--------------------|----------------------------|--|
|                    |                            | Plaintext authentication and MD5 authentication for OSPF and RIPv2 packets |
|                    |                            | Public Key Infrastructure (PKI)  |
|                    |                            | IP Source Guard  |
| 18                 | IEEE                       | IEEE 802.3x  |
|                    |                            | IEEE 802.3ad   |
|                    |                            | IEEE 802.3af   |
|                    |                            | IEEE 802.3at   |
|                    |                            | IEEE 802.3bz   |
|                    |                            | IEEE 802.1p  |
|                    |                            | IEEE 802.1x  |
|                    |                            | IEEE 802.1q  |
|                    |                            | IEEE 802.1d  |
|                    |                            | IEEE 802.1w  |
| IEEE 802.1s        |                            |  |
| 19                 | Loading and upgrading      | Loading and upgrading through XMODEM/FTP/TFTP                              |
|                    |                            | Loading and upgrading from USB   |
| 20                 | Management and maintenance | Configuration through CLI, Telnet, and console port                        |
|                    |                            | SNMP v1/v2/v3  |
|                    |                            | Web network management   |
|                    |                            | Remote Monitoring (RMON) alarm, event, and history recording               |
|                    |                            | IMC network management system  |
|                    |                            | System log, alarming based on severity, debugging information output       |
|                    |                            | NTP, SNTP  |
|                    |                            | Power, fan, and temperature alarming                                       |
|                    |                            | Ping and Tracert   |
|                    |                            | Virtual Cable Test (VCT)   |
|                    |                            | Device Link Detection Protocol (DLDP)                                      |
|                    |                            | LLDP, LLDP-MED   |
| Loopback detection |                            |  |
| 21                 | Power saving               | Automatic port power-down  |
|                    |                            | Scheduled port power-down (schedule job)                                   |
|                    |                            | 802.3az Energy Efficient Ethernet (EEE) support                            |

**(Annexure E)**

| <b>Annex-E</b> |                               | <b>Access Switches</b>  |                               |                               |
|----------------|-------------------------------|---|-------------------------------|-------------------------------|
| <b>Sr. No</b>  | <b>Description</b>            | <b>Required</b>   |                               |                               |
|                | <b>Features</b>               | <b>10 Port Access Switch</b>  | <b>28 Ports Access Switch</b> | <b>52 Ports Access Switch</b> |
| 1              | Switching capacity            | 20Gbps  | 56Gbps                        | 104Gbps                       |
| 2              | Packet forwarding rate        | 15Mpps  | 41.7Mpps                      | 77.4Mpps                      |
| 3              | Fixed ports                   | 8*10/100/1000TX   | 24*10/100/1000TX              | 48*10/100/1000TX              |
|                |                               | +2*SFP  | +4*SFP                        | +4*SFP                        |
| 4              | Operating temperature         | 0°C to 45°C   |                               |                               |
| 5              | Operating humidity            | 10% RH to 95% RH, non-condensing  |                               |                               |
| 6              | Stacking                      | Intelligent Resilient Framework 2 (IRF2)  |                               |                               |
| 7              | Link aggregation              | 1G/10GE port aggregation  |                               |                               |
|                |                               | Static aggregation  |                               |                               |
|                |                               | Dynamic aggregation   |                               |                               |
|                |                               | Multichassis link aggregation   |                               |                               |
| 8              | Jumbo frame                   | Supported   |                               |                               |
| 9              | MAC address table             | Blackhole MAC Address MAC learning limit  |                               |                               |
| 10             | Flow control                  | 802.3x flow control and half-duplex backpressure                                    |                               |                               |
| 11             | VLAN                          | Port-based VLAN QinQ  |                               |                               |
|                |                               | Voice VLAN  |                               |                               |
|                |                               | MAC VLAN  |                               |                               |
| 12             | ARP                           | ARP Detection   |                               |                               |
|                |                               | ARP speed limit   |                               |                               |
| 13             | ND                            | Supported   |                               |                               |
| 14             | VLAN virtual port             | Supported   |                               |                               |
| 15             | DHCP                          | DHCP Client   |                               |                               |
|                |                               | DHCP Snooping   |                               |                               |
|                |                               | DHCP Relay  |                               |                               |
|                |                               | DHCP Server   |                               |                               |
|                |                               | DHCP Option82   |                               |                               |
| 16             | DNS                           | Static and Dynamic DNS IPV4 and IPV6  |                               |                               |
| 17             | Routing protocols             | IPV4/IPV6 static routing RIP/ RIPng, OSPFV1/V2/V3                                   |                               |                               |
| 18             | Multicast                     | IGMP Snooping V1/V2/V3  |                               |                               |
|                |                               | MVR   |                               |                               |
| 19             | Strom suppression             | Storm suppression based on port bandwidth percentage Storm suppression based on PPS |                               |                               |
| 20             | Layer 2 ring network protocol | STP/RSTP/MSTP   |                               |                               |
|                |                               | STP Root Protection   |                               |                               |
|                |                               | Smart Link  |                               |                               |
|                |                               | RRPP  |                               |                               |

|                    |                            |  |
|--------------------|----------------------------|--|
| 21                 | Mirroring                  | Flow mirroring   |
|                    |                            | Port mirroring   |
| 22                 | QoS/ACL                    | Packet filter  |
|                    |                            | Flexible queue scheduling algorithms based on ports and queues, including SP, WRR and SP+WRR Bidirectional ACL |
|                    |                            | Port-based speed limit Flow redirection  |
| 23                 | Security                   | Time-range   |
|                    |                            | Hierarchical user management and password protection MAC- based authentication                                 |
|                    |                            | 802.1X   |
|                    |                            | SSH2.0   |
|                    |                            | Port isolation   |
|                    |                            | IP source guard  |
| 24                 | IEEE                       | HTTPs  |
|                    |                            | EAD  |
|                    |                            | IEEE 802.3x  |
|                    |                            | IEEE 802.3ad   |
|                    |                            | IEEE 802.3af   |
|                    |                            | IEEE 802.3at   |
|                    |                            | IEEE 802.1p  |
|                    |                            | IEEE 802.1x  |
|                    |                            | IEEE 802.1q  |
|                    |                            | IEEE 802.1d  |
| IEEE 802.1w        |                            |  |
| IEEE 802.1s        |                            |  |
| 25                 | Loading and upgrading      | Loading and upgrading through FTP/TFTP   |
| 26                 | Management and maintenance | Configuration from CLI   |
|                    |                            | Login through Telnet, and the console port   |
|                    |                            | Simple Network Management Protocol (SNMP)  |
|                    |                            | Remote Monitoring (RMON)   |
|                    |                            | IMC network management system  |
|                    |                            | WEB management   |
|                    |                            | System log   |
|                    |                            | Alarming based on severity   |
|                    |                            | IRF  |
|                    |                            | NTP  |
|                    |                            | Debugging information output   |
|                    |                            | Telnet-based remote maintenance  |
|                    |                            | NQA  |
| DLDP               |                            |  |
| Virtual Cable Test |                            |  |

| Annex-D                        |   | Wi-Fi Controller  |                             |
|--------------------------------|---|---|-----------------------------|
| Sr. No                         | Description                             | Required  |                             |
| <b>Hardware specifications</b> |   |   |                             |
| 1                              | Throughput                              | 8Gbps   |                             |
| 2                              | Port                                    | 8 GE+SFP combo  |                             |
|                                |   | 2 SFP+  |                             |
|                                |   | 1 console   |                             |
| 3                              | Power supplies                          | 1 AC power supply included, swappable power supply, 1+1 redundant backup (separately ordered) |                             |
| 4                              | Max power consumption                   | <300W   |                             |
| 5                              | Operating and storage temperature       | 0°C~45°C/-40°C~70°C   |                             |
|                                | Operating and storage relative humidity | 5%~95%  |                             |
| 7                              | Safety Compliance                       | UL 60950-1  |                             |
|                                |   | CAN/CSA C22.2 No 60950-1  |                             |
|                                |   | IEC 60950-1   |                             |
|                                |   | EN 60950-1/A11  |                             |
|                                |   | AS/NZS 60950  |                             |
|                                |   | EN 60825-1  |                             |
|                                |   | EN 60825-2  |                             |
|                                |   | EN60601-1-2   |                             |
|                                |   | FDA 21 CFR Subchapter J   |                             |
| 8                              | EMC                                     | ETSI EN 300 386 V1.3.3:2005   |                             |
|                                |   | EN 55024: 1998+ A1: 2001 + A2: 2003   |                             |
|                                |   | EN 55022 :2006  |                             |
|                                |   | VCCI V-3:2007   |                             |
|                                |   | ICES-003:2004   |                             |
|                                |   | EN 61000-3-2:2000+A1:2001+A2:2005   |                             |
|                                |   | EN 61000-3-3:1995+A1:2001+A2:2005   |                             |
|                                |   | AS/NZS CISPR 22:2004  |                             |
|                                |   | FCC PART 15:2005  |                             |
|                                |   | GB 9254:1998  |                             |
|                                |   | GB/T 17618:1998   |                             |
| <b>Software specifications</b> |   |   |                             |
| 9                              | Basic functions                         | Number of managed APs by default  | 0                           |
|                                |   | Size of license   | 1/4/8/16/32/64/128/512/1024 |
|                                |   |   | 512                         |

|                  |                                     |  |  |
|------------------|-------------------------------------|--|--|
|                  |                                     | Maximum number of managed Aps                |  |
|                  |                                     | Maximum number of STA                        | 8192   |
| 10               | 802.11MAC                           | 802.11 Protocols                             | Supported  |
|                  |                                     | Multi-SSID (Per RF)                          | 16   |
|                  |                                     | SSID hiding                                  | Supported  |
|                  |                                     | 11G protection                               | Supported  |
|                  |                                     | 11n only                                     | Supported  |
|                  |                                     | Use number limit                             | Supported: SSID based, per RF based              |
|                  |                                     | Keep-alive                                   | Supported  |
|                  |                                     | Idle   | Supported  |
|                  |                                     | Multi-country code assignment                | Supported  |
|                  |                                     | Wireless user isolation                      | Supported:                                       |
|                  |                                     |  | VLAN based wireless users 2-layer isolation      |
|                  |                                     |  | SSID based wireless user 2-layer isolation       |
|                  |                                     | 20MHz/40MHz auto-switch in 40MHz mode        | Supported:                                       |
| Local forwarding | Local forwarding based on SSID+VLAN |  |  |
| 11               | CAPWAP                              | Auto AP serial number entry                  | Supported:                                       |
|                  |                                     | AC discovery (DHCP option43, DNS)            | Supported:                                       |
|                  |                                     | IPv6 tunnel                                  | Supported:                                       |
|                  |                                     | Clock synchronization                        | Supported:                                       |
|                  |                                     | Jumbo frame forwarding                       | Supported:                                       |
|                  |                                     | Assign basic AP network parameter through AC | Supported: Static IP, VLAN, connected AC address |
|                  |                                     | L2/L3 connection between AP and AC           | Supported:                                       |
|                  |                                     | NAT traversal between AP and AC              | Supported:                                       |
| 12               | Roaming                             | Intra-AC, Inter-AP L2 and L3 roaming         | Supported:                                       |
|                  |                                     | Inter-AC, Inter-AP L2 and L3 roaming         | Supported:                                       |
| 13               | GW features                         | NAT  | Supported:                                       |
|                  |                                     | PPPoE  | Supported:                                       |
|                  |                                     | DDNS   | Supported:                                       |
|                  |                                     | IPSEC VPN                                    | Supported:                                       |
|                  |                                     | SSL VPN                                      | Supported:                                       |
|                  |                                     | GRE  | Supported:                                       |
| 14               | Access control                      | Open system, Shared-Key                      | Supported:                                       |
|                  |                                     | WEP-64/128, dynamic WEP                      | Supported:                                       |

|    |     |   |   |
|----|-----|---|---|
|    |     | WPA, WPA2, WPA3   | Supported:  |
|    |     | TKIP  | Supported:  |
|    |     | CCMP  | Supported:  |
|    |     | SSH v1.5/v2.0   | Supported:  |
|    |     | Wireless EAD (End-point Access Domination)                    | Supported:  |
|    |     | Portal authentication   | Supported: Remote Authentication, external server   |
|    |     | Portal page redirection                                       | Supported: SSID based, AP Portal page push  |
|    |     | Portal by-pass Proxy  | Supported:  |
|    |     | 802.1x authentication   | EAP-TLS, EAP-TTLS, EAP-PEAP, EAP-MD5, EAP-SIM, LEAP, EAP-FAST, EAP offload (TLS, PEAP only) |
|    |     | Local authentication  | 802.1X, Portal, MAC authentication  |
|    |     | LDAP authentication   | 802.1X and Portal<br>EAP-GTC and EAP-TLS supported by 802.1X login                          |
|    |     | AP location-based user access control                         | Supported:  |
|    |     | Guest Access control  | Supported:  |
|    |     | VIP channel   | Supported:  |
|    |     | ARP attack detection  | Supported: Wireless SAVI  |
|    |     | SSID anti-spoofing  | SSID + user name binding  |
|    |     | AAA server selection based on SSID and domain                 | Supported:  |
|    |     | AAA server back up  | Supported:  |
|    |     | Local AAA server for wireless user                            | Supported:  |
|    |     | TACACS+   | Supported:  |
| 15 | QoS | Priority mapping  | Supported:  |
|    |     | L2-L4 packet filtering and traffic classification             | Supported:  |
|    |     | Rate limit  | Supported with granularity of 8Kbps   |
|    |     | 802.11e/WMM   | Supported:  |
|    |     | Access control based on user profile                          | Supported:  |
|    |     | Intelligent bandwidth limit (equal bandwidth share algorithm) | Supported:  |
|    |     | Intelligent bandwidth limit (user specific)                   | Supported:  |

|    |                  |  |  |
|----|------------------|--|--|
|    |                  | Intelligent bandwidth guarantee        | Supported: Free flow for packets coming from every SSID When traffic is not congested, and guarantee a minimum bandwidth for each SSID when traffic is congested |
|    |                  | QoS Optimization for SVP phone         | Supported:   |
|    |                  | CAC (Call Admission Control)           | Supported: based on user number/bandwidth  |
|    |                  | End-to-end QoS                         | Supported:   |
|    |                  | AP upload speed limit                  | Supported:   |
| 16 | RF management    | Country code lock                      | Supported:   |
|    |                  | Static channel and power configuration | Supported:   |
|    |                  | Auto channel and power configuration   | Supported:   |
|    |                  | Auto transmission rate adjustment      | Supported:   |
|    |                  | Coverage hole detection and correction | Supported:   |
|    |                  | Load balancing                         | Supported: based on traffic, user & frequency (dual frequency supported)   |
|    |                  | Intelligent load balancing             | Supported:   |
|    |                  | AP load balancing group                | Supported: auto-discovery and flexible setting   |
| 17 | Security         | Static blacklist                       | Supported:   |
|    |                  | Dynamic blacklist                      | Supported:   |
|    |                  | White list                             | Supported:   |
|    |                  | Rogue AP detection                     | Supported: SSID based, BSSID, device OUI and more  |
|    |                  | Rogue AP countermeasure                | Supported:   |
|    |                  | Flooding attack detection              | Supported:   |
|    |                  | Spoof attack detection                 | Supported:   |
|    |                  | Weak IV attack detection               | Supported:   |
|    |                  | WIPS                                   | Supported: 7-layer mobile security   |
| 18 | Layer 2 protocol | ARP (gratuitous ARP)                   | Supported:   |
|    |                  | 802.1p                                 | Supported:   |
|    |                  | 802.1q                                 | Supported:   |
|    |                  | 802.1x                                 | Supported:   |
| 19 | IP protocol      | IPv4 protocol                          | Supported:   |
|    |                  | Native IPv6                            | Supported:   |
|    |                  | IPv6 SAVI                              | Supported:   |
|    |                  | IPv6 Portal                            | Supported:   |
|    |                  | DHCP Server (IPv4, IPv6)               | Supported:   |



|    |                           |   |   |
|----|---------------------------|---|---|
| 20 | Multicast                 | MLD Snooping  | Supported:  |
|    |                           | IGMP Snooping                                       | Supported:  |
|    |                           | Multicast group                                     | 256   |
|    |                           | Multicast to Unicast (IPv4, IPv6)                   | Supported: Set unicast limit based on operating environment |
| 21 | Redundancy                | 1+1 failover between ACs                            | Supported:  |
|    |                           | Intelligent AP sharing among ACs                    | Supported:  |
|    |                           | Remote AP   | Supported:  |
| 22 | Management and deployment | Network management                                  | WEB, SNMP v1/v2/v3, RMON and more                           |
|    |                           | Network deployment                                  | WEB, CLI, Telnet, FTP and more                              |
| 23 | Wi-Fi location            | CUPID location                                      | Supported:  |
| 24 | Green features            | Scheduled shutdown of AP RF interface               | Supported:  |
|    |                           | Scheduled shutdown of wireless service              | Supported:  |
|    |                           | Per-packet power adjustment (PPC)                   | Supported:  |
| 25 | WLAN application          | RF Ping   | Supported:  |
|    |                           | Remote probe analysis                               | Supported:  |
|    |                           | Real Time Spectrum Guard (RTSG)                     | Supported:  |
|    |                           | Wireless Intelligent Application Aware (WIAA)       | Supported/ Stateful Inspection Firewall                     |
|    |                           | Packet forwarding fairness adjustment               | Supported:  |
|    |                           | 802.11n packet forwarding suppression               | Supported:  |
|    |                           | Access based traffic shaping                        | Supported:  |
|    |                           | Co-AP channel sharing                               | Supported:  |
|    |                           | Co-AP channel reuse                                 | Supported:  |
|    |                           | RF interface transmission rate adjustment algorithm | Supported:  |
|    |                           | Drop wireless packet with weak signal               | Supported:  |
|    |                           | Disable user access with weak signal                | Supported:  |
|    |                           | Disable multicast packet caching                    | Supported:  |
|    |                           | Status blink (limited to some AP)                   | Supported:  |
| 26 | New added features        | Policy forwarding                                   | Supported:  |
|    |                           | VLAN pool   | Supported:  |
|    |                           | Bonjour gateway                                     | Supported:  |
|    |                           | 802.11w   | Supported:  |
|    |                           | 802.11k   | Supported:  |
|    |                           | Hotspot2.0 (802.11u)                                | Supported:  |

|  |  |     |            |
|--|--|-----|------------|
|  |  | NAT | Supported: |
|  |  | VPN | Supported: |

**(Annexure G)**

| <b>Annex-G</b>                 |                                      | <b>Access Point</b>   |
|--------------------------------|--------------------------------------|---|
| <b>Sr. No</b>                  | <b>Description</b>                   | <b>Required</b>   |
| <b>Hardware specifications</b> |                                      |   |
| 1                              | Ethernet ports                       | Two (one for 100/1000M/2.5G Rj45, one for 100/1000M Rj45 support IoT) support LACP (support between both network ports for redundancy and increased capacity)   |
| 2                              | PoE                                  | Port1: 2.5GE:802.3at/802.3af Port2: GE: PSE,802.3af   |
| 3                              | Local Power supply                   | 54V DC  |
| 4                              | Console port                         | One (RJ-45) One USB 2.0   |
| 5                              | Built-in antenna                     | Built-in omni-directional antenna Radio 1: 5dBi antenna gain @ 5G Radio 2: 5dBi antenna gain @ 5G<br>Radio 3: 5dBi antenna gain @ 2.4G or 5dBi antenna gain @ 5G  |
| 6                              | Built-in Bluetooth                   | Built-in Bluetooth (Support to switch RFID through software), support iBeacon standard  |
| 7                              | IoT Extension                        | Support BLE, RFID, ZigBee etc.  |
| 8                              | Working frequencies                  | 802.11ax/ac wave2/ac/n/a: 5.725GHz-5.850 GHz; 5.47~5.725GHz; 5.15~5.35GHz<br>802.11ax/b/g/n: 2.4GHz-2.483GHz  |
| 9                              | Modulation technology                | OFDM: BPSK@6/9Mbps, QPSK@12/18Mbps, 16-QAM@24Mbps, 64-QAM@48/54Mbps<br>DSSS: DBPSK@1Mbps, DQPSK@2Mbps,<br>CCK@5.5/11Mbps (file://dbpsk@1mbps, dqpsk@2mbps, cck@5.5/11Mbps) MIMO-OFDM (11n) : MCS 0-31<br>MIMO-OFDM (11ac) : MCS 0-11 MIMO-OFDM (11ax) : MCS 0-11                          |
| 10                             | Modulation mode                      | 11b : DSS: CCK@5.5/11Mbps, DQPSK@2Mbps, DBPSK@1Mbps<br>11a/g: OFDM:64QAM@48/54Mbps,16QAM@24Mbps, QPSK@12/18Mbps, BPSK@6/9Mb<br>Ps<br>11n : MIMO-OFDM: BPSK, QPSK,16QAM,64QAM<br>11ac : MIMO-OFDM: BPSK, QPSK,16QAM,64QAM,256QAM<br>11ax: MIMO-OFDM: BPSK, QPSK,16QAM,64QAM,256QAM,1024QAM |
| 11                             | Maximum transmit power               | 20 dBm (Transmit power is multi-chain combined power, no antenna gain is included. The actual transmit power depends on local laws and regulations)   |
| 12                             | Adjustable power granularity         | 1dBm  |
| 13                             | Reset/restoration to factory default | Supported   |
| 14                             | State LED                            | Alternating flashing mode, orange/green/blue for different working states, breathing mode   |

|                                   |   |   |   |
|-----------------------------------|---|---|---|
| 15                                | Working Temperature/<br>Storage Temperature | -10°C~55°C (32°F to 113°F)/-40°C~70°C (-40°F to +158°F)   |   |
| 16                                | Working Humidity/<br>Storage Humidity       | 5%~95%(non-condensing)  |   |
| 17                                | Protection class                            | IP42  |   |
| 18                                | Overall power<br>consumption                | ≤34W (excluding IoT modules)  |   |
| 19                                | Safety compliance                           | GB4943、EN60601-1-2(medical electrical equipment) 、UL/CSA 60950-1、EN/IEC 60950-1、EN/IEC 60950-22 |   |
| 20                                | EMC   | GB9254、EN301 489、EN55022、FCC Part 15、RSS-210  |   |
| 21                                | Radio frequency<br>certification            | FCC Part 15、EN 300 328、EN 301 893、and MIIT SRRC   |   |
| 22                                | Health                                      | FCC Bulletin OET-65C、EN 50385、IC Safety Code 6  |   |
| 23                                | MTBF  | >250000H  |   |
| <b>Software specifications</b>    |   |   |   |
| 24                                | Compliance                                  | 802.11  | Indoor, compliant with 802.11a/b/g/n/ac/ac wace2/ax |
| 25                                | 802.11ax                                    | Working frequencies and MIMO  | 1. 5G (1) 2*2 MIMO 1.2Gbps+5G (2) 2*2 MIMO          |
|                                   |   |   | 1.2Gbps+5G (3) 2*2 MIMO 0.867Gbps                   |
|                                   |   |   | 2. 5G (1) 2*2 MIMO 1.2Gbps+5G (2) 2*2 MIMO          |
|                                   |   |   | 1.2Gbps+2.4G 2*2 MIMO 0.4Gbps                       |
|                                   |   |   | 3. 5G (1) 2*2 MIMO 1.2Gbps+2.4G 2*2 MIMO            |
|                                   |   |   | 0.575Gbps+5G (2) 2*2 MIMO 0.867Gbps                 |
|                                   |   |   | 4. 5G (1) 2*2 MIMO 1.2Gbps+2.4G (1) 2*2 MIMO        |
|                                   |   |   | 0.575Gbps+2.4G (2) 2*2 MIMO 0.4Gbps                 |
|                                   |   | 20MHz/40MHz bandwidth   | Supported   |
|                                   |   | 80MHz bandwidth   | Supported   |
|                                   |   | Maximum transmission speed  | 5G (1):1.2Gbps                                      |
|                                   |   |   | 5G (2):1.2Gbps                                      |
|                                   |   |   | 2.4G: 400Mbps/5G:( can be adjusted to 5G: 867Mbps)  |
|                                   |   | A-MPDU  | Supported   |
| A-MSDU                            | Supported                                   |   |   |
| Maximum likelihood decoding (MLD) | Supported                                   |   |   |
| Maximum ratio combining (MRC)     | Supported                                   |   |   |
|                                   | Supported                                   |   |   |
| Space-time block coding           | Supported                                   |   |   |

|    |                 |   |  |                                       |           |
|----|-----------------|---|--|---------------------------------------|-----------|
|    |                 | (STBC)  |  |                                       |           |
|    |                 | Low-density parity-check (LDPC)                           | Supported  |                                       |           |
|    |                 | Cyclic Delay Diversity (CDD)/Cyclic Shift Diversity (CSD) | Supported  |                                       |           |
|    |                 | Repeater mode   | Supported  |                                       |           |
| 26 | Security policy | Encryption  | WEP-64/128/152bit, dynamic WEP, TKIP, CCMP, AES, EAP, WPA3   |                                       |           |
|    |                 |   | Multiple triggering conditions for unicast and broadcast key update  |                                       |           |
|    |                 | 802.11i   | Supported  |                                       |           |
|    |                 | Authentication  | 802.1X authentication, MAC authentication, PSK authentication, Portal authentication, PPSK<br>Access controllers might be required for authentication. |                                       |           |
|    |                 | User isolation  | Layer 2 user isolation<br>SSID-based user isolation  |                                       |           |
|    |                 | Forwarding security                                       | Packet filtering<br>MAC address filtering Broadcast storm suppression  |                                       |           |
|    |                 | Wireless terminal access                                  | Wireless EAD   |                                       |           |
|    |                 | SSID and VLAN binding                                     | Supported  |                                       |           |
|    |                 | Rogue device detection and countermeasure                 | Supported  |                                       |           |
|    |                 | Dynamic ARP Inspection (DAI)                              | Supported  |                                       |           |
|    |                 | IP Source Guard (IPSG)                                    | Supported  |                                       |           |
|    |                 | WIDS/WIPS   | Supported  |                                       |           |
|    |                 | Management frame protection (802.11w)                     | Supported  |                                       |           |
|    |                 | 27  | AAA  | RADIUS client                         | Supported |
|    |                 |   |  | Multiple domain authentication server | Supported |
|    |                 |   |  | Backup authentication                 | Supported |

|  |   |                                      |   |
|--|---|--------------------------------------|---|
|  |   | server                               |   |
| 28   | Layer 2 and Layer 3 features  | IP address configuration             | Static IP (available only in fat AP mode)<br>DHCP assigned IP (Option 60) |
|  |   | Native IPv6                          | Supported   |
|  |   | IPv6 Portal                          | Supported   |
|  |   | IPv6 SAVI                            | Supported   |
|  |   | ACL                                  | IPv4/IPv6   |
|  |   | Local forwarding                     | Local forwarding based on SSID and VLAN                                   |
|  |   | Link Layer Discovery Protocol (LLDP) | Supported   |
|  |   | SSID-based VLAN assignment           | Supported   |
|  |   | EoGRE Tunnel                         | Supported   |
|  |   | Multicast                            | IGMP Snooping/MLD Snooping  |
|  |   | 29                                   | QoS   |
| Priority   | 802.1p priority and marking on Ethernet ports                         |                                      |   |
|  | Priority mapping for wired and wireless packets                       |                                      |   |
| QoS policy mapping   | SSID/VLAN and QoS policy mapping                                      |                                      |   |
| Layer 2 to Layer 4 packet filtering and traffic classification | Supported   |                                      |   |
| CAR  | Supported   |                                      |   |
| Client bandwidth management                                    | Station-based bandwidth allocation<br>SSID-based bandwidth allocation |                                      |   |
| Load balancing   | Traffic-based load balancing  |                                      |   |
|  | Session-based load balancing  |                                      |   |
|  | Frequency-based load balancing (supports dual-band)                   |                                      |   |
| Band navigation  | Supported   |                                      |   |
| Multicast optimization (IPv4/IPv6)                             | Supported   |                                      |   |
| Call Admission Control (CAC)                                   | Session-based CAC<br>Channel usage-based CAC                          |                                      |   |
| Airtime optimization   | Supported   |                                      |   |
| Airtime fairness   | Supported   |                                      |   |

|    |                            |  |  |
|----|----------------------------|--|--|
|    |                            | Layer 4-7 application identification                                     | The APs can identify variety of applications and policy control can be implemented including priority adjustment, scheduling, blocking, and rate limiting on users |
|    |                            | SVP Phone  | Supported  |
| 30 | Power saving               | PPC  | Supported  |
|    |                            | Green AP mode  | Supported  |
|    |                            | Dynamic MIMO power saving  | Supported  |
|    |                            | E-APSD   | Supported  |
|    |                            | WMM Power Save   | Supported  |
| 31 | Management and maintenance | Network management   | Trap, HTTP(S), SSH, Telnet, FTP/TFTP, SNMP V1/V2/V3<br>only applicable in Cloud/Fat mode   |
|    |                            | Management SSID  | Supported  |
|    |                            | Syslog   | Supported  |
|    |                            | AP Working Mode  | Fit/Anchor/Cloud/Fat   |
|    |                            | Remote probing and analysis  | Supported  |
| 32 | Wi-Fi Certified            | IEEE 802.11a/b/g/n/ac/ax, WMM, WPA, WPA2 and WPA3 – Enterprise, Personal |  |
|    |                            | (SAE), Enhanced Open (OWE), Wi-Fi Alliance                               |  |

(Annexure H)

| Annex-H |   | Secure web Gateway |
|---------|---|--------------------|
| Sr. No  | Description   | Required           |
|         | <b><u>Secure Web Gateway</u></b>  |                    |
| 1       | <b><u>General Requirement</u></b>   |                    |
|         | · Must Be Listed in 2020 Gartner Magic Quadrant for Secure Web Gateway  | Supported          |
|         | · Must Have Minimum 160Mbps Live Throughput (All Features Enabled)  | Supported          |
|         | · Must Have Minimum 60,000 Concurrent Users   | Supported          |
|         | · Must Have Minimum 128GB SSD Storage Capacity  | Supported          |
|         | · Must Have Minimum 6 x 1G Ethernet Interface   | Supported          |
|         | · Must have (Bypass) Copper 1 Pair  | Supported          |
|         | · Must Quote 1 Years Traffic Control Features License   | Supported          |
|         | · Must Quote 1 Years Software Upgrade & 24x7 Technical Support  | Supported          |
|         | · Must Quote 1 Years Hardware Warranty Service  | Supported          |
| 2       | <b><u>User Authentication &amp; Management</u></b>  | Supported          |
|         | · Must Have User Identification Base on IP Address, MAC Address, Hostname   | Supported          |
|         | · Must Have User Binding Base on IP Address and MAC Address   | Supported          |
|         | · Must Have Identification of Endpoint such as Mobile, PC and etc.  | Supported          |
|         | · Must Have SMS Authentication, Captive Portal and etc.   | Supported          |
|         | · Must Have Captive Portal Integration with Microsoft Active Directory  | Supported          |
|         | · Must Have Customizable Captive Portal HTML Page   | Supported          |
|         | · Must Have URL Redirection After Captive Portal Authentication   | Supported          |
|         | · Must Have Single Sign-On (SSO) Authentication Base on Active Directory, Radius, POP3 and other Database Servers | Supported          |
|         | · Must Have QR Code Authentication with Self-Registration Capability  | Supported          |



**(Annexure I)**

| <b>Annex-I</b> |   | <b><u>NMS</u></b> |
|----------------|---|-------------------|
| <b>Sr. No</b>  | <b>Description</b>  | <b>Required</b>   |
| 1              | <b>Simple and Effort less Monitoring</b>  | Supported         |
|                | Agentless monitoring for Windows, Linux, and macOS  | Supported         |
|                | Auto-discovery – immediate visualization of discovered devices  | Supported         |
|                | Preconfigured templates for common devices and applications   | Supported         |
|                | Automatic software updates  | Supported         |
|                | Simple and fair licensing model including an easy upgrade path  | Supported         |
| 2              | <b>Flexible and reliable alerts</b>   | Supported         |
|                | Alerts for individually configured criteria   | Supported         |
|                | Various notification methods (email, Slack, HTTP request, Microsoft Teams, push notifications, exe, script, syslog, etc.) | Supported         |
|                | Scheduled and customizable reports (HTML, PDF)  | Supported         |
|                | Detailed log files about all activities   | Supported         |
| 3              | <b>One solution for everything</b>  | Supported         |
|                | Support for all common standards (SNMP, ICMP, WMI, HTTP, SSH, REST, OPC UA, etc.)   | Supported         |
|                | Support for NetFlow and IPFIX, sFlow, jFlow and packet sniffing   | Supported         |
|                | Monitoring of hardware, software, virtual environments, and applications  | Supported         |
|                | Event log monitoring  | Supported         |
|                | Monitoring of multiple sites with one license   | Supported         |
| 4              | <b>Data publication</b>   | Supported         |
|                | Drag & drop map editor for individualized dashboards  | Supported         |
|                | Integrated reporting engine with delivery as HTML, PDF, or CSV  | Supported         |
|                | Fully featured API (Access monitoring data and manipulate monitoring objects using HTTP requests)                         | Supported         |
|                | Powerful interactive web interface  | Supported         |
|                | Desktop app for viewing multiple installations in one dashboard   | Supported         |

**(Annexure J)**

| <b>Annex-J</b> |   | <b>Servers</b>  |
|----------------|---|-----------------|
| <b>Sr. No</b>  | <b>Description</b>  | <b>Required</b> |
|                | <b>Server-1</b>   |                 |
|                | 8SFF CTO Server   | Supported       |
|                | 2 x (1.9GHz/6Cores/8.25MB/85W) CPU Module   | Supported       |
|                | 2 x 32GB 2Rx4 DDR4-3200 CAS-22-22-22 RDIMM Memory Module                          | Supported       |
|                | 8SFF HDD Cage Module BAY2   | Supported       |
|                | 2 x 600GB 12G SAS 10K 2.5in EP 512n HDD General Intelligent Disk Equipment Module | Supported       |
|                | 2 x 1.2TB 12G SAS 10K 2.5in EP HDD General Intelligent Disk Equipment Module      | Supported       |
|                | FHHL Riser Card (Slot 1/2) (3 X8 FHHL)  | Supported       |
|                | 12Gb 2 Ports SAS RAID Card (8 SAS Ports,1GB Cache, No Power Fail Safeguard)       | Supported       |
|                | Power Fail Safeguard Module (with Supercap)                                       | Supported       |
|                | 4-Port GE Copper Interface MLOM(X722) Ethernet Adapter                            | Supported       |
|                | 2 x 550W AC & 240V HVDC Power Supply (LT-R1-Platinum)                             | Supported       |
|                | SAS HD Transit Cable,0.83m, SAS HD 72pinS, SAS Cable,2*(SAS HD 36pinA)            | Supported       |
|                | ASSY, CORD, AC, IEC TO IEC  | Supported       |
|                | Power Cable with straight mode connector (3m, type G), for England                | Supported       |
|                | 2U Standard Fan Module  | Supported       |
|                | 2U Standard Rail-A  | Supported       |
|                |   |                 |
|                | <b>Server-2</b>   |                 |
|                | 8SFF CTO Server   | Supported       |
|                | 2 x (3.0GHz/8Cores/11MB/115W) CPU Module  | Supported       |
|                | 2 x 32GB 2Rx4 DDR4-3200 CAS-22-22-22 RDIMM Memory Module                          | Supported       |
|                | 8SFF HDD Cage Module BAY2   | Supported       |
|                | 2 x 600GB 12G SAS 10K 2.5in EP 512n HDD General Intelligent Disk Equipment Module | Supported       |
|                | 480GB 6G SATA 2.5in MU S4610 SSD Generic Module-i                                 | Supported       |
|                | FHHL Riser Card (Slot 1/2) (3 X8 FHHL)  | Supported       |
|                | 12Gb 2 Ports SAS RAID Card (8 SAS Ports,1GB Cache, No Power Fail Safeguard)       | Supported       |
|                | Power Fail Safeguard Module (with Supercap) (2U LSI RAID)                         | Supported       |
|                | 4-Port GE Copper Interface MLOM(X722) Ethernet Adapter,360T L3                    | Supported       |
|                | 2 x 550W AC & 240V HVDC Power Supply (LT-R1-Platinum)                             | Supported       |
|                | SAS HD Transit Cable,0.83m, SAS HD 72pinS, SAS Cable,2*(SAS HD 36pinA)            | Supported       |
|                | ASSY, CORD, AC, IEC TO IEC  | Supported       |
|                | Power Cable with straight mode connector (3m, type G), for England                | Supported       |
|                | 2U Standard Fan Module  | Supported       |
|                | 2U Standard Rail-A  | Supported       |

**(Annexure K)**

| <b>Annex-K</b> |  | <b><u>SAN Storage</u></b> |
|----------------|--|---------------------------|
| <b>Sr.No</b>   | <b>Description</b>   | <b>Required</b>           |
| 1              | Storage Array  | Supported                 |
|                | 12Gb SAS 8 Port Dual Controller  | Supported                 |
|                | Rack Rails 2U  | Supported                 |
|                | ME Series 2U Bezel   | Supported                 |
|                | Power Supply, 580W, Redundant  | Supported                 |
|                | ProSupport and 4-hour Mission Critical-ACDTS, 36 Month(s)                  | Supported                 |
|                | Parts Only Warranty 36 Months-ACDTS, 36 Month(s)                           | Supported                 |
|                | 12 x 8TB Hard Drive SAS ISE 12Gbps 7.2K 512e 3.5in Hot-Plug                | Supported                 |
|                | 2 x Power Cord - C13, 1.9M, 250V, 10A (Indonesia, Laos, Pakistan, Vietnam) | Supported                 |

**(Annexure L)**

| <b>Annex-L</b> |  | <b><u>Laptop</u></b> |
|----------------|--|----------------------|
| <b>Sr.No</b>   | <b>Description</b>   | <b>Required</b>      |
| 1              | Processor: 11th Gen i5                                       | Supported            |
|                | Graphic/Display: 14" FHD (1920 x 1080) AG Non-Touch, 250nits | Supported            |
|                | Memory: 2X8 GB (16 GB) 3200MHz DDR4                          | Supported            |
|                | Hard Drive: M.2 512 GB PCIe Solid State Drive                | Supported            |
|                | OS: Licensed Windows 10 Professional or higher               | Supported            |
|                | Network / Ethernet & wireless LAN                            | Supported            |
|                | Warranty: General Warranty                                   | Supported            |
|                | Bag: Branded Essential Laptop bag                            | Supported            |

**(Annexure M)**

| <b>Annex-M - Fire Detection System</b> |   | <b><u>Fire Detection</u></b> |
|--|---|------------------------------|
| <b>Sr.No</b>                           | <b>Description</b>  | <b>Required</b>              |
| 1                                      | <p>Fire Detection System with extinguishers.</p> <p>Civil Work:</p> <p>Dumpa Ceiling as per below room size</p> <p>Ceiling Lights 2x 2 qty 6 with electric wiring.</p> <p>IT room Size: 16 x 23 feet.</p> |                              |

(Annexure N)

| <b>Annex-N</b>  | <b>UPS</b>      |
|---|-----------------|
| <b>Description</b>  | <b>Required</b> |
| 5 KVA UPS backup systems for Server Room<br>Backup Time Required: 4 Hours at least<br>Equipment's on backup: 3 Server system with Racks, Routers, Switches,<br>Firewall, SAN Storage etc.<br>Description: Trolley / Rack for UPS and Batteries<br>Brand: International / European |                 |

(Annexure O)

| <b>Passive Items</b> |  |                        | <b>Unit</b> |
|----------------------|--|------------------------|-------------|
| <b>1</b>             | CAT 6 I/O  | 3M/ Schneider/Aitek    | No          |
| <b>2</b>             | 3-meter Fiber Patch Cord.  | China                  | No          |
| <b>3</b>             | CAT 6 Face Plate and Back Box  | 3M/ Schneider/Aitek    | No          |
| <b>4</b>             | CAT 6 Cable Roll. (305 meter)  | 3M/ Schneider/Aitek    | No          |
| <b>5</b>             | CAT 6 1meter Patch Cord.   | 3M/ Schneider/Aitek    | No          |
| <b>6</b>             | 24 Port patch Panel with I/O   | 3M/ Schneider/Aitek    | No          |
| <b>7</b>             | Cabinet 6U with PDU  | Local                  | No          |
| <b>8</b>             | Cabinet 9U with PDU  | Local                  | No          |
| <b>9</b>             | Cabinet 42U with PDU -along with 8 port KVM switch and drawer  | Local/imported         | No          |
| <b>10</b>            | Power Socket   | Schneider              | No          |
| <b>11</b>            | Power Cable 3.29 dual core. (90 meter)   | FAST/ GM or equivalent | No          |
| <b>12</b>            | Cable Manager  |                        | No          |
| <b>13</b>            | Duct 16x25   | Adamjee / GM           | FT          |
| <b>14</b>            | Duct 16x38   | Adamjee / GM           | FT          |
| <b>15</b>            | Duct 40x40   | Adamjee / GM           | FT          |
| <b>16</b>            | <b>e)</b> Active and Passive Items installation including Configuration, Commissioning and Testing.<br><b>f)</b> Soft/Hard Digging of Fiber including HDPE Pipe, warning tape, Hand Hole, fiber Joints Enclosures, splicing, marker post and reinstate of roads/pavements.<br><b>g)</b> Power Earthing/Grounding of server room.<br><b>h)</b> 10 days extensive training of GKMC/BKMC ICT staff on installed equipment's and deployed solutions. Preparation and sharing of required user manuals/troubleshooting guide for the installed equipment's. | 1-Job                  | Job         |

---

**Thank You**